

## Safety

- High accuracy:  $\pm 2\%$
- Fast start function against start delay
- Anti-bolus function
- Water proof level: IP24
- Long runtime battery

## Friendliness

- Intuitive keypad
- Parameters enlarge function
- DPS, Dynamic pressure show
- Automatic calibration



## EN-S3 Syringe Pump

## EN-S3 Syringe Pump

Model	EN-S3
Syringe sizes	5ml,10ml,20ml,30ml,50/60ml
Flow rate accuracy	±2%
Flow rate	0.1-1500 ml/h
VTBI	0-9999 ml
Dose rate units	More than 15 types
Concentration calculate	Automatically
Parameters enlarge	Support
Purge	Support
Titration	Support
Bolus setting	Manual bolus Programmable bolus
KVO rate	0.1-5.0 ml/h
Infusion modes	3 infusion mode
Micro mode	Support
Standby mode	Support,standby time 0-23h59m adjustable
Drug library	Support, more than 60
Keypad lock	Support
Brightness	Adjustable
Alarm volume	Adjustable
Occlusion levels	3 levels
Anti-bolus	Automatically
Records	More than 2000 entries
Alarms	VTBI near end, VTBI infused, Pressure high, Battery nearly empty, Battery empty, No power supply, Reminder alarm, KVO finished
Power supply	AC: 110V-240V, 50/60Hz DC: 12V
Battery life	Approx. 12 hours (at 5ml/h flow rate with new fully charged battery)
Classification	Class I, CF
Water proof	IP24
Calibration	Automatically
Display	2.8 inch colour TFT
Input	Keypad
Interface	MINI USB
Wireless	WIFI ( optional )
Weight	Approx. 1.7kg

